

CEWELD OA 50

TYPE C-, Cr-, Si, Mn- Alloyed flux cored wire on parts wich subjected to abrasive wear and medium impact

APPLICATIONS Rebuilding and or protecting parts that faces abrasion with medium impact

PROPERTIES High C-, Cr- alloyed flux-cored wire electrode which forms extremely hard carbides for extremely hard deposits on parts subject to excessively heavy abrasive wear weldable without protective gas. More than 3 layers should not be deposited. A Buffer layer with CEWELD[®] OA 4370 or CEWELD[®] OA MnCr is recommended in case of old layers or critical base metals.. Equivalent in SMAW: CEWELD[®] Dur 62S

CLASSIFICATION EN ISO 14700: T Fe16

SUITABLE FOR Trash crushing, impact resistant

APPROVALS No Approvals Found

WELDING POSITIONS


  

TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)	C	Si	Mn	Cr	Fe
	3.2	1.8	1.8	16	Rem.

ALL WELD MECHANICAL PROPERTIES	Heat Treatment	R _{p0,2} MPa	R _m MPa	A ₅ (%)	Hardness Rockwell C
	As Welded /				Avg. 52

REDRYING TEMPERATURE 140°C / 24 hr

GAS ACCORDING EN 14175



CEWELD OA 50

OA 50 1,6MM

Type	KG/unit	EANCode
BS-300	15	8720663403629