



# CEWELD OA WC2 Fe

|                       |   |
|-----------------------|---|
| <b>TYPE</b>           | Iron based flux cored wire for hardfacing containing a high amount of fused tungsten carbides.  |
| <b>APPLICATIONS</b>   | This fused tungsten carbide based alloy provides an excellent resistance against extreme abrasion wear. OA WC2-Fe can be applied on most type of steels except on cast iron or Mn-steel. This alloy is the most wear resistant type in almost any hardfacing application.   |
| <b>PROPERTIES</b>     | 2400 HV Iron and Tungsten based hardfacing alloy containing 52-58% (depending on wire diameter) tungsten carbides. OA WC2-Fe has good welding characteristics. Multi-layer deposits are not recommended due to the extreme high hardness. Fused tungsten carbide will guaranty a long life for several wear applications. Best to be used without gas protection (self shielded). |
| <b>CLASSIFICATION</b> | EN ISO                    14700: T Fe20<br>DIN                        8555: MF 21-GF-65-GZ  |
| <b>SUITABLE FOR</b>   | Rebuilding of stabilisers and other oilfield tools where maximum protection against abrasion is required. Also for augers, impellers, mixer plates in the brick and clay industry and on decanter screws or hardfacing deep drilling equipment.   |
| <b>APPROVALS</b>      | No Approvals Found  |

**WELDING POSITIONS**



**TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)**

WSC  
56

**ALL WELD MECHANICAL PROPERTIES**

| Heat Treatment | R <sub>p0,2</sub><br>MPa | R <sub>m</sub><br>MPa | A5<br>(%) | Hardness<br>Vickers |
|----------------|--------------------------|-----------------------|-----------|---------------------|
| As Welded /    |                          |                       |           | Avg. 2400           |

**REDRYING TEMPERATURE** 140°C / 24 hr

**GAS ACCORDING EN 14175**



# CEWELD OA WC2 Fe

OA WC2 FE 1,6MM

| Type   | KG/unit | EANCode       |
|--------|---------|---------------|
| BS-300 | 15      | 8720663403834 |

OA WC2 FE 2,4MM

| Type   | KG/unit | EANCode       |
|--------|---------|---------------|
| BS-300 | 15      | 8720663403858 |