





TYPE GMAW welding wire for corrosion resistant C22 type of alloys.

APPLICATIONS CEWELD® NiCrMo 622 is used for welding of nickel-chromium-molybdenum alloys as well as for

> overlay cladding on carbon, low alloy, or stainless steels. They are also used for dissimilar joints between nickel-chromium-molybdenum alloys and stainless, carbon, or low alloyed steels. Also recommended for joining Molybdenum-containing stainless steels, low alloyed steels and dissimilar

welding between earlier mentioned type of steels.,

PROPERTIES CEWELD® NiCrMo 622 offers excellent corrosion resistance in oxidizing as well as reducing media in

a wide variety of chemical process environments. It offers an outstanding resistance to stress

corrosion cracking, pitting and crevice corrosion.

CLASSIFICATION **AWS** A 5.14: ERNiCrMo-10

> EN ISO 18274: S Ni 6022(NiCr21Mo13Fe4W3)

F-nr 43 FΜ 6 W.Nr. 2.4635

SUITABLE FOR Nickel-based alloys such as alloy 22 or similar materials, dissimilar welding of nickel-based alloys

to each other

M no: 2.4602, 2.4605, 2.4610, 2.4819, 2.4856, 1.4565

NiCr23Mo16Al, NiCr21Mo14W, NiMo16Cr15W, NiMo16Cr16Ti, NiCr22Mo9Nb, X2CrNiMnMoNbN25-18-

5-4, X1NiCrMoCuN25-20-7,

Alloy 59, Alloy C22, Alloy C-276, Alloy C-4, Alloy 625, Alloy 24, Alloy 904hMo

UNS: N06059, N06022, N10276, N06455, N0625, S34565

AL6XN, F574, B619, B622 and B626

W86022, N06022

APPROVALS No Approvals Found

WELDING POSITIONS



TYPICAL CHEMICAL AN ME

IT ICAL CITEMICAL	C	31	IVIII	l Ci	INI	1410	
NALYSIS OF THE FILLER	0.008	0.08	0.3	22	55	13.5	Γ
ETAL (%)		l				1	

ALL WELD MECHANICAL **PROPERTIES**

Heat	R _{P0,2}	Rm	A5	Impact Energy (J) ISO-V	Hardness
Treatment	MPa	MPa	(%)	-196°C	Vickers
As Welded /	500	740	44	130	Avg. 220

REDRYING TEMPERATURE Not required

GAS ACCORDING EN 14175 11 Co





CEWELD NiCrMo 622

NICRMO 622 0,2MM	Type	KG/unit	EANCode
	D-100	0,1	8720663424310
NICRMO 622 1,0MM	Type	KG/unit	EANCode
	BS-300	15	8720663418661
NICRMO 622 1,2MM	Туре	KG/unit	EANCode
	BS-300	15	8720663418678
NICRMO 622 1,6MM	Туре	KG/unit	EANCode
	BS-300	15	8720663418685