




# CEWELD E Guts

TYPE	Special coated electrode with hard blowing effect for gouging.
APPLICATIONS	CEWELD E Guts is suitable for all materials that has conductivity, it is used on aluminium, cast iron, steel, copper, nickel etc. Guts can be a solution in cases where a cutting flame will produce too much heat or at hardly reachable places. Also it can be very useful on materials that cannot be flame cut such as stainless steel.
PROPERTIES	Chamfering instructions: Guts can be used on high amps and must have an angle of about 15 degrees (almost flat) to give the best results. The working speed when making grooves can be improved by making slightly pushing movements in one direction. Guts B2 has a non conductive coating for excellent applicability in hard to reach places.
CLASSIFICATION	
SUITABLE FOR	Gouging, Drilling holes, Remove old weld metal, Chamfering, Cutting, Weld preparations etc.
APPROVALS	No Approvals Found
WELDING POSITIONS	
REDRYING TEMPERATURE	Not required
GAS ACCORDING EN 14175	



# CEWELD E Guts

E GUTS 2,5 X 350MM

Type	KG/unit	EANCode
Can	2,2	8720663420848

E GUTS 3,2 X 350MM

Type	KG/unit	EANCode
Can	2	8720663420855

E GUTS 4,0 X 350MM

Type	KG/unit	EANCode
Can	2,6	8720663420862

E GUTS 5,0 X 350MM

Type	KG/unit	EANCode
Can	2,2	8720663420879