



## CEWELD CroNi 29-9 S

**TYPE** 29-9 welding electrode for buffer layers, dissimilar welding and difficult to weld steels. (Type 29 9,

312, 1.4337)

**APPLICATIONS** CEWELD® CroNi 29-9 S is an austenitic-ferritic special alloy that is suitable for joining difficult-to-

> weld steels. It has a wide range of applications such as the repair and maintenance of machines, shafts and gear wheels, particularly in the construction machinery sector. It is also excellent for buffer layers before overlay welding and for dissimilar welds between steel, stainless steels or unknown steels. Very good corrosion resistance in damp, sulphurous environments, e.g. in sulphate

digesters in the paper industry.

**PROPERTIES** CEWELD® CroNi 29-9 S is very popular because of its soft, stable arc and its easy spatter-free

application with very good slag removal without residues. High corrosion resistance and high

temperature resistance up to 1100 °C with excellent weldability at both AC and DC+.

A 5.4: E 312-16 CLASSIFICATION **AWS** 

> EN ISO 3581-A: E 29 9 R 12

F-nr 5 FΜ 5 1.4337 W.Nr.

SUITABLE FOR ISO 15608: 8 > 19% Cr Type: 29% Cr, 9%Ni

1.4762, 1.4085

X120Mn12, X10Cr13, GX32CrNi28-10, GX49CrNi27-4, GX8CrCrNiN26-7, X3CrNiMoN27-5-2, X 10

CrAl 24, G-X 70 Cr 29

UNS S41000

AISI 329, 410. S235, E295

Hss, C45, C60, dissimilar welding S335 - X120Mn12, maintenance, buffer layers, repairing cock wheels, 42MnV7, 25CrMo4, 42CrMo4, 50CrMo4, 1.5223, 1.7218, 1.7225, 1.7228, Armox, Hardox

**APPROVALS** CE

WELDING POSITIONS



TYPICAL CHEMICAL ANALYSIS OF WELD METAL

(%)

C	Sı	Mn	P	S	Cr	Nı	FN
0.1	0.8	1.5	0.02	0.015	30	9	38

ALL WELD MECHANICAL **PROPERTIES** 

Heat	R <sub>P0,2</sub>	Rm	A5	Impact Energy (J) ISO-V	Hardness
Treatment	MPa	MPa	(%)	RT	Brinell Hardness
As Welded /	500	750	23	40	Avg. 300

REDRYING TEMPERATURE 300°C / 2 hr

**GAS ACCORDING EN 14175** 





## CEWELD CroNi 29-9 S

CRONI 29-9 S 1,6 X 250MM	Type	KG/unit	EANCode	
	Can	2,1	8720663416322	
CRONI 29-9 S 2,0 X 300MM	Туре	KG/unit	EANCode	
	Can	2,4	8720663416339	
CRONI 29-9 S 2,5 X 300MM	Type	KG/unit	EANCode	
	Can	2,4	8720663416346	
CRONI 29-9 S 3,2 X 350MM	Type	KG/unit	EANCode	
_	Can	2,5	8720663416353	
		1		
CRONI 29-9 S 4,0 X 350MM	Туре	KG/unit	EANCode	
_	Can	2,5	8720663416360	_
		1		
CRONI 29-9 S 5,0 X 350MM	Туре	KG/unit	EANCode	
_	Can	2,5	8720663416377	
		· · · · · · · · · · · · · · · · · · ·		