



CEWELD Powder 8812-Co-45

certilas® THE FILLER METAL SPECIALIST

TYPE	Agglomerated and sintered Tungsten carbide-cobalt powder for Thermal Spraying					
APPLICATIONS	CEWELD 8812-Co-45 is an carbide powder for wear resistant coatings produced by flame-, plasma or high-velocityflame-spraying (HVOF). Used to protect against abrasion and friction. Steel Rolls, Conveyor Screws, Impellor Screws, Corrugating Rollers, Exhaust Fans, Pump Housings					
PROPERTIES	CEWELD 8812-Co-45 the dense and smooth layers with hardness of up to 1200 HV0.1 and tensile strength acc. to DIN 50160 of more than 70 MPa are frequently used without further treatment. Coating thickness should not exceed 300 µm. Maximum operating temperature is 540°C (1004°F). Powder type: agglomerated and sintered Primary WC carbide size: 2.5 µm FSSS Apparent density (ISO 3923-2): 4.2-5.5 g/cm ³ Particle shape: preponderantly spherical Particle size: 45/20 µm					
CLASSIFICATION	EN ISO	14232-1 WC-Co 88/12				
SUITABLE FOR	Ideal for use in a wide variety of high wear applications in-cluding erosion, abrasion and sliding wear. High chrome like finishes can be obtained by typical grinding or lapping techniques.					
APPROVALS	No Approvals Found					
WELDING POSITIONS						
TYPICAL CHEMICAL ANALYSIS OF WELD METAL (%)	C	0.1	Co	12	WC	88
REDRYING TEMPERATURE	Not required					
GAS ACCORDING EN 14175						